


# **Heavy-Duty Flooring**





**RMG Polyvinyl India Limited,** an ISO 9001:2015 systems approved company and is one of the largest manufacturer and exporter of PVC Floor Coverings in India with annual production in excess of 40,000MT (27 Million Sq meters) of residential & heavy duty floorings. Winner of Top Export Award for PVC floor Coverings since several years, the products are exported to Asian countries, Europe, Gulf, Africa and the Americas.

RMG's state-of-the-art plant is located at Sikandarabad (UP) in the Delhi NCR region, the capital of India. The factory boasts of modern calendaring, LVT & cushion vinyl lines to deliver the widest range of flooring products which meet international requirements for abrasion, low smoke & fire retardant properties.

The factory also produces PVC leather, PVC Films & PVC Geomembranes.

RMG's flooring is marketed in India and overseas under the flagship brand WONDERFLOOR. The Wonderfloor product range includes floorings for home interiors, offices, education, healthcare, factories, buses & rail coaches, aerobridges, supermarkets, porta cabins, prefabricated shelters and almost all interior applications.











Thickness: 1.00/1.50mm/2.00mm/3.00mm

Roll Width: 1.50 mtr

Roll Length: 15 / 20 linear mtr

# ROBUST Multi-Purpose Floorings

Robust is heavy duty, high quality, resilient, flexible and highly durable marbled PVC Flooring. It is designed to withstand high traffic and abrasion. This product has a unique marbling pattern that adds to the aesthetics of the area where they are installed as it is produced having one base colour and two contrast colours used for marbling by a special hot granulation process which is unique in nature.

The product is specially treated with a "Wonderguard" surface treatment which ensures scratch resistance, resistance to staining, easy maintenance & very easy cleaning of shoe scuff marks.


#### Salient Features

- Robust office flooring is 'P' rated and have a slip resistance of R9
- The floorings are embossed with "Raindrop" embossing design which enables quick cleaning & easy maintenance.
- · Robust is available with PUR surface **protection** providing resistance against scratches & dirt accumulation and also ensures quick cleaning/ mopping
- Can be thermo welded for joint free installation
- Application areas: Offices, Shops, Factories, Porta Cabins, Auditoriums, schools, libraries, healthcare etc.

1.00mm does not come with PUR Surface Protection

## PUR SURFACE PROTECTION

Ice Land





Wonderfloor's Robust Flooring incorporates WONDERGUARD state-of-the-art-technology, which have exhibited 99.9% inhibition in growth of microbial activity under test conditions and also support clean condition requirements for hygiene.



Thickness: 1.50/2.00mm/3.00mm Roll Width: 1.5 mtr / 2 mtr Roll Length: 15 / 20 linear mtr

# SIGGMA COMMERCIAL

Multi-Purpose Floorings

SIGGMA - COMMERCIAL is a specialized flooring designed for commercial projects/industry keeping in mind the heavy footfalls, trolley movements etc. It has standard antimicrobial / fungicidal properties of the Vinyl flooring.


The product is specially treated with a "Wonderguard" surface treatment which ensures scratch resistance, resistance to staining, easy maintenance & very easy cleaning of shoe scuff marks.

#### Salient Features

- Siggma Commercial office flooring is 'P' rated and have a slip resistance of R9
- Siggma Commercial is available with PUR surface protection providing resistance against scratches & dirt accumulation and also ensures quick cleaning/mopping
- Can be thermo welded for joint free installation
- Application areas: Pharma Shops, Medical Factories, Dispensaries, Clean rooms, Offices & Food industry etc.

# PUR SURFACE PROTECTION

Steel Grey





Wonderfloor's **Siggma Commercial** incorporates **WONDERGUARD** state-of-the-art-technology, which have exhibited 99.9% inhibition in growth of microbial activity under test conditions and also support clean condition requirements for hygiene.

### Installed at:


- Daikin AC factory IIT-Mumbai PGI, Chandigarh Fisher Scientific Sports Authority of India, Lucknow
  Amausi International Hospital Hindustan Aeronautical Ltd Prime Surgicals Bharat Biotec Labs, Hyderabad
  Torrent Pharmaceutical Ahmedabad Bank Note Press Zydus Healthcare, Hyderabad Nuclear Power Corp
  NTPC Canara Bank Allahabad Bank Videocon International











# PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	ROBUST	DUROFLOOR	SIGGMA COMMERCIAL
THICKNESS (mm)	EN 428 / ISO 24346	1.00/1.50/2.00/3.00	1.00/1.50/2.00/3.00	1.50/2.00/3.00
ROLL WIDTH (mtr)	EN 426 / ISO 24341	1.50 / 2.00	1.50 / 2.00	1.50 / 2.00
ROLL LENGTH (mtr)	EN 426 / ISO 24341	15 / 20	15 / 20	15/20
TILE SIZE (mm)	EN 427	300x300/305x305/610x610*	300x300/305x305/610x610*	300x300 /305x305/610x610*
TOTAL WEIGHT (kgs/sq mtr)	EN 430 / ISO 23997	1.80/2.70/3.60/5.40	1.85/2.80/3.75/5.60	2.65/3.50/5.25
SURFACE PROTECTION	PUR	PUR PROTECTION (Except 1mm)	PUR PROTECTION-OPTIONAL	PUR PROTECTION
SLIP RESISTANCE	DIN 51130 / ASTM D2047	R9 / PASS	R9 / PASS	R9 / PASS
HYGIENE / CLEAN ROOM TEST	ISO 14644-1	Inhibits Growth of Microbes, Class A	Inhibits Growth of Microbes, Class A	Inhibits Growth of Microbes, Class A
RESIDUAL INDENTATION (mm)	EN 433 / ISO 23343-1	≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm
FLEXIBILITY (mm)	EN 435 / ISO 24344	40 mm MANDREL. PASS	40 mm MANDREL. PASS	40 mm MANDREL. PASS
DIMENSIONAL STABILITY (%)	EN 434 / ISO 23999	≤ 0.40%	≤ 0.40%	≤ 0.40%
BEARING CASTOR CHAIR	EN 425 / ISO 4918	SUITABLE / CONTINUOUS	SUITABLE / CONTINUOUS	SUITABLE / CONTINUOUS
FIRE PROPAGATION	BS 476 PART 6	(I)=10.8 (II)=1.7 } CLASS "0"	(I)=10.8 (II)=1.7 } CLASS "0"	(I)=10.8 (II)=1.7 } CLASS "0"
SURFACE SPREAD OF FLAME	BS 476 PART 7	CLASS 1	CLASS 1	CLASS1
HORIZONTAL & VERTICAL BURNING TEST	IS 15061 - 2002	PASS (ARAI)	PASS (ARAI)	PASS (ARAI)
REACTION TO FIRE (kw/m2)	EN ISO 9239-1	> 8 / PASS BfI-S1	>8 / PASS BfI-S1	> 8 / PASS BfI-S1
PERFORMANCE CLASSIFICATION	EN 685 / ISO 10874	34, 41	32, 33	34,41
ABRASION RESISTANCE	EN: 660-2	WEAR GROUP P	WEAR GROUP M	WEAR GROUP P
SOUND ABSORPTION	ISO 140-8/EN 1SO 717-2	△ LW = 4db	△ LW = 5db	△ LW = 4db
THERMAL RESISTANCE (m2k/w)	EN 12664 / ISO 8302	<0.00568 - PASS	<0.00568 - PASS	<0.00568 - PASS
STAIN RESISTANCE	EN 423 / ISO 26987	O, EXCELLENT RESISTANCE	1, VERY GOOD RESISTANCE	1, VERY GOOD RESISTANCE
COLOUR FASTNESS	ISO 105-B02	> BLUE WOOL STANDARD 5	> BLUE WOOL STANDARD 5	> BLUE WOOL STANDARD 5
MARITIME USAGES		SUITABLE	SUITABLE	SUITABLE

<sup>\*</sup> Against Bulk Order











### MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail: mkt@rmgpoly.com

or call: +91 9711200510

For export enquiries, please e-mail: info@rmgpoly.com

or call: +91 9873138885 / +91 9953208740

#### RMG POLYVINYL INDIA LIMITED

Registered Office: UGSR 4, Ansals Plaza, Sector 1, Vaishali Ghaziabad 201 010, (U.P) INDIA. Tel.: +91

120-4284802/803/804/805/806.

Fax: +91 11 66173679. E-mail: info@rmgpoly.com

#### **Regional Offices:**

- Ahmedabad Bangalore Bhubaneswar Chennai Chandigarh• Guwahati Hyderabad Indore Kolkata Kochi
- · Lucknow · Mumbai · Pune · Patna

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited www.wonderfloor.com



